

Order Code: XCBDL10NW  
10W - Recessed Backlit Downlight - 4000K



Features

- Suitable for corridors, reception areas, indoor circulation spaces, retail, toilets and shower rooms
- Available in 2 different outputs
- More consistent and uniform appearance than traditional edge-lit panels or downlights
- Up to 85 lumens per watt efficacy

Construction

- Plastic housing and reflector
- Integral driver
- Loop in/out 2-pole terminal
- IP54 Rated

Technical Data

| General                       |         | Electrical                |                   |
|-------------------------------|---------|---------------------------|-------------------|
| Luminaire Wattage (W)         | 10      | Rated Input Current (A)   | 0.12              |
| Weight (kg)                   | 0.17    | Power Factor (pf)         | 0.9               |
| Operating Temperature (ta °C) | 0 to 25 | Input Voltage Range (VAC) | 85-265            |
| Light Output                  |         | Inrush Current Peak (A)   | 27.6              |
|                               |         | Surge Protection (kV)     | 0.5               |
|                               |         | Conductor Size (mm)       | 2.5               |
| Lumens (lm)                   | 850     | Terminal Type             | 2 pole screw down |
| Efficacy (lm/W)               | 85      |                           |                   |
| LED                           |         |                           |                   |
| CCT (K)                       | 4000    |                           |                   |
| CRI                           | 80      |                           |                   |
| Macadam Elipses               | 4       |                           |                   |

**Order Code:** XCBDL10NW  
10W - Recessed Backlit Downlight - 4000K

Dimensions

|              |     |
|--------------|-----|
| C (mm)       | 82  |
| Cut Out (mm) | 90  |
| Dia. (mm)    | 115 |

Line Drawing

