

Order Code: XCBH12CT

12W - Circular Bulkhead - IP65 - CCTK Selector [3000K/4000K/6000K] - White



Features

- Ideal for retrofit of existing 2D fixtures
- Suitable for bathrooms or storerooms
- Microwave movement sensor available
- CCT adjustable via 3-way selector switch [3000K/4000K/6000K]
- Up to 92 lumens per watt efficacy

Construction

- Polycarbonate body
- Polished Chrome finish available
- Integral emergency option available



Technical Data

General		Electrical	
Luminaire Wattage (W)	12	Rated Input Current (A)	0.07
Weight (kg)	0.85	Power Factor (pf)	0.7
Operating Temperature (ta °C)	0 to 25	Input Voltage Range (VAC)	220-240
		Inrush Current Peak (A)	10
Light Output		Surge Protection (kV)	1
Lumens (lm)	1000 to 1100	Conductor Size (mm)	2.5
Efficacy (lm/W)	92	Terminal Type	3 pole piano key
LED			
CCT (K)	3000K/4000K/6000K		
CRI	80		
Macadam Elipses	4		

Order Code: XCBH12CT

12W - Circular Bulkhead - IP65 - CCTK Selector [3000K/4000K/6000K] - White

Dimensions

C (mm)	110
Dia. (mm)	330

Line Drawing

