
xcite LED Lighting

Data Sheet



Order Code: XCBH12CTM3GT

XCITE RETRO FIT GEAR TRAY XCBH 14W - Fixed output - Emergency - 3000K-6500K



Features

- CCT [3000K/4000K/6500K] adjustable via 3-way selector switch
- Microwave movement sensor available
- Up to 148 lumens per watt efficacy

Construction

Emergency option available

Installation Notes

Universal fitting suitable for various circular enclosures













Technical Data

General			
Luminaire Wattage (W)	14.2	_	
Weight (kg)	0.38	_	
Operating Temperature (to °C)	0 to 25	_	
Light Output		-	
Lumens (lm)	2100	-	
Efficacy (Im/W)	148	-	
LED -			
CRI	80		
Macadam Elipses	3		
Driver			
Driver Current (mA)	350		
Forward Voltage (V)	32.6		
Emergency			
Emergency Lumen Operating	155		
Emergency Wattage (W)	1		

Electrical		
Rated Input Current (A)	0.09	
Power Factor (pf)	0.72	
Input Voltage Range (VAC)	198 - 264	
Inrush Current Peak (A)	292	
Surge Protection (kV)	1 kV	
Conductor Size (mm)	0.5 to 2.5	
Terminal Type	SLK series 4 to pole grip to wire	



xcite LED Lighting

Data Sheet



Order Code: XCBH12CTM3GT

XCITE RETRO FIT GEAR TRAY XCBH 14W - Fixed output - Emergency - 3000K-6500K

Dimensions

C (mm)	40
Dia. (mm)	265

Line Drawing

