
xcite LED Lighting

Data Sheet



Order Code: XCBH12CTM3HFSGT

XCITE RETRO FIT GEAR TRAY XCBH 14W - Fixed output - Emergency - Microwave sensor - 3000K-6500K



Features

- Microwave movement sensor available
- CCT [3000K/4000K/6500K] adjustable via 3-way selector switch
- Up to 148 lumens per watt efficacy

Construction

Emergency option available

Installation Notes

Universal fitting suitable for various circular enclosures















Technical Data

General		
Luminaire Wattage (W)	14.2	Rated
Weight (kg)	0.43	
Operating Temperature (ta °C)		Input \
Light Output		Inrush
Lumens (Im)	2100	Surge
Efficacy (lm/W)		Condu
LED		Termir
CRI	80	
Macadam Elipses	3	
Driver		
Driver Current (mA)	350	
Forward Voltage (V)	32.6	
Emergency		
Emergency Lumen Operating	155	
Emergency Wattage (W)	1	

Electrical		
Rated Input Current (A)	0.09	
Power Factor (pf)	0.72	
Input Voltage Range (VAC)	198 - 264	
Inrush Current Peak (A)	292	
Surge Protection (kV)	1 kV	
Conductor Size (mm)	0.5 to 2.5	
Terminal Type	SLK series 4 to pole grip to wire	

xcite LED Lighting

Data Sheet



Order Code: XCBH12CTM3HFSGT

XCITE RETRO FIT GEAR TRAY XCBH 14W - Fixed output - Emergency - Microwave sensor - 3000K-6500K

Dimensions

C (mm)	40
Dia. (mm)	 265

Line Drawing

