xcite LED Lighting

Data Sheet



Order Code: XCBH12CTM3PC

12W - Circular Bulkhead - IP65 - 3hr Maintained Emergency - CCTK Selector [3000K/4000K/6000K] - Polished Chrome

Features



- Suitable for bathrooms or storerooms
- Microwave movement sensor available
- CCT [3000K/4000K/6000K] adjustable via 3-way selector switch
- Up to 92 lumens per watt efficacy

Construction

- · Polycarbonate body
- Polished Chrome finish available
- Integral emergency option available



















Technical Data

Technical Data			
General		Electrical	
Luminaire Wattage (W)	12	Rated Input Current (A)	0.07
Weight (kg)	1.15	Power Factor (pf)	0.7
Operating Temperature (ta °C)	5 to 25	Input Voltage Range (VAC)	220-240
Light Output		Inrush Current Peak (A)	10
Light Output Lumens (lm)	1000-1100 92	Surge Protection (kV)	1
Efficacy (Im/W)		Conductor Size (mm)	2.5
Lineacy (iii) vv)		Terminal Type	4 pole screw down
LED			
CCT (K)	TRI-COLOUR		
CRI	80		
Macadam Elipses	4		
Emergency			
Emergency Lumen Operating	140		
Emergency Wattage (W)	2		

xcite LED Lighting

Data Sheet



Order Code: XCBH12CTM3PC

12W - Circular Bulkhead - IP65 - 3hr Maintained Emergency - CCTK Selector [3000K/4000K/6000K] - Polished Chrome

Dimensions

C (mm)	110
Dia. (mm)	330

Line Drawing



