

Order Code: XCBH12CTM3PC
12W - Circular Bulkhead - IP65 - 3hr Maintained Emergency - CCTK Selector [3000K/4000K/6000K] - Polished Chrome



Features

- Ideal for retrofit of existing 2D fixtures
- Suitable for bathrooms or storerooms
- Microwave movement sensor available
- CCT [3000K/4000K/6000K] adjustable via 3-way selector switch
- Up to 92 lumens per watt efficacy

Construction

- Polycarbonate body
- Polished Chrome finish available
- Integral emergency option available



Technical Data

General	
Luminaire Wattage (W)	12
Weight (kg)	1.15
Operating Temperature (ta °C)	5 to 25
Light Output	
Lumens (lm)	1000-1100
Efficacy (lm/W)	92
LED	
CCT (K)	TRI-COLOUR
CRI	80
Macadam Ellipses	4
Emergency	
Emergency Lumen Operating	140
Emergency Wattage (W)	2

Electrical	
Rated Input Current (A)	0.07
Power Factor (pf)	0.7
Input Voltage Range (VAC)	220-240
Inrush Current Peak (A)	10
Surge Protection (kV)	1
Conductor Size (mm)	2.5
Terminal Type	4 pole screw down

Order Code: XCBH12CTM3PC
12W - Circular Bulkhead - IP65 - 3hr Maintained Emergency - CCTK Selector [3000K/4000K/6000K] - Polished Chrome

Dimensions

C (mm)	110
Dia. (mm)	330

Line Drawing

