

Order Code: XCBH12CTPC

12W - Circular Bulkhead - IP65 - CCTK Selector [3000K/4000K/6000K] - Polished Chrome

**Features**

- Ideal for retrofit of existing 2D fixtures
- Suitable for bathrooms or storerooms
- Microwave movement sensor available
- CCT [3000K/4000K/6000K] adjustable via 3-way selector switch
- Up to 92 lumens per watt efficacy

Construction

- Polycarbonate body
- Polished Chrome finish available
- Integral emergency option available

Technical Data**General**

| | |
|-------------------------------|---------|
| Luminaire Wattage (W) | 12 |
| Weight (kg) | 0.85 |
| Operating Temperature (ta °C) | 0 to 25 |

Light Output

| | |
|-----------------|-----------|
| Lumens (lm) | 1000-1100 |
| Efficacy (lm/W) | 92 |

LED

| | |
|------------------|------------|
| CCT (K) | TRI-COLOUR |
| CRI | 80 |
| Macadam Ellipses | 4 |

Electrical

| | |
|---------------------------|------------------|
| Rated Input Current (A) | 0.07 |
| Power Factor (pf) | 0.7 |
| Input Voltage Range (VAC) | 220-240 |
| Inrush Current Peak (A) | 10 |
| Surge Protection (kV) | 1 |
| Conductor Size (mm) | 2.5 |
| Terminal Type | 3 pole piano key |

Order Code: XCBH12CTPC

12W - Circular Bulkhead - IP65 - CCTK Selector [3000K/4000K/6000K] - Polished Chrome

Dimensions

| | |
|-----------|-----|
| C (mm) | 110 |
| Dia. (mm) | 330 |

Line Drawing

