

### Order Code: XCBHCBOX1M3MS

X1 Bulkhead WP - Circular - Opal diffuser - CCT [3000K/4000K/6000K]+ Wattage Selectable - Black - Emergency - Microwave sensor



#### Features

- Suitable for exterior commercial and industrial applications
- Wattage selectable via selector switch [8W/12W/16W]
- CCT selectable via selector switch [3000K/4000K/6000K]

#### Construction

- Modular [emergency](#) and [microwave sensor](#)'s available for quick and easy conversion of a standard fitting
- For additional control, please use [X1 Bulkhead Remote](#) [Sold Separately]

#### Installation Notes

3-point screw fixing  
Conduit side entry points for surface mount cable entry  
Loop-in, loop-out push-fit terminal block for quick tool-free instalation



#### Technical Data

| General                       |                   | Electrical                |                  |
|-------------------------------|-------------------|---------------------------|------------------|
| Luminaire Wattage (W)         | 8W/12W/16W        | Rated Input Current (A)   | 0.04 to 0.08     |
| Weight (kg)                   | 0.82              | Power Factor (pf)         | 0.83 to 0.92     |
| Operating Temperature (ta °C) | 5° to 25°         | Input Voltage Range (VAC) | 198 to 264       |
|                               |                   | Inrush Current Peak (A)   | 19.1             |
| Light Output                  |                   | Surge Protection (kV)     | 1                |
| Lumens (lm)                   | 1070 to 1930      | Conductor Size (mm)       | 0.5 to 2.5       |
| Efficacy (lm/W)               | 128               | Terminal Type             | 4 pole piano key |
| LED                           |                   |                           |                  |
| CCT (K)                       | 3000K/4000K/6000K |                           |                  |
| CRI                           | 80                |                           |                  |
| Macadam Ellipses              | 1 to 1.5          |                           |                  |
| Driver                        |                   |                           |                  |
| Driver Current (mA)           | 140/215/280       |                           |                  |
| Forward Voltage (V)           | 48.5 to 52.5      |                           |                  |
| Emergency                     |                   |                           |                  |
| Emergency Lumen Operating     | 146               |                           |                  |
| Emergency Wattage (W)         | 2                 |                           |                  |

**Order Code: XCBHCBOX1M3MS**

X1 Bulkhead WP - Circular - Opal diffuser - CCT [3000K/4000K/6000K]+ Wattage Selectable - Black - Emergency - Microwave sensor

Dimensions

|           |     |
|-----------|-----|
| C (mm)    | 85  |
| Dia. (mm) | 282 |

Line Drawing

