

### Order Code: XCBHLX1WM3

X1 Bulkhead Large - White - CCT [3000K/4000K/6000K] + Wattage Selectable [12/16/20W] - Fixed output - Opal diffuser - Fixed output - Emergency



#### Features

- Suitable for most domestic and commercial applications
- CCT selectable via selector switch [3000K/4000K/6000K]
- Wattage selectable via selector switch [12W/16W/20W]

#### Construction

- Large 435mm diameter bulkhead
- Manufactured from durable thermoplastic materials
- Modular [emergency](#) and [microwave sensor](#)'s available for quick and easy conversion of a standard fitting
- For additional control, please use [X1 Bulkhead Remote](#) [Sold Separately]
- Pre-assembled emergency and sensor luminaires available

#### Installation Notes

Loop in/out push-fit terminal block for quick installation



#### Technical Data

General		Electrical	
Luminaire Wattage (W)	12W/16W/20W	Rated Input Current (A)	0.05 to 0.09
Weight (kg)	1.38	Power Factor (pf)	0.96 to 0.98
Operating Temperature (ta °C)	5° to 25°	Input Voltage Range (VAC)	220 to 240
		Inrush Current Peak (A)	20
		Surge Protection (kV)	1KV
		Conductor Size (mm)	0.5 to 2.5
		Terminal Type	4 pole piano key
Light Output			
Lumens (lm)	1800/2500/3000		
Efficacy (lm/W)	150		
LED			
CCT (K)	3000K/4000K/6000K		
CRI	80		
Macadam Elipses	3.7 to 11		
Driver			
Driver Current (mA)	90, 120, 155		
Forward Voltage (V)	110 to 114.1		
Emergency			
Emergency Lumen Operating	97		
Emergency Wattage (W)	1		

### Order Code: XCBHLX1WM3

X1 Bulkhead Large - White - CCT [3000K/4000K/6000K] + Wattage Selectable [12/16/20W] - Fixed output - Opal diffuser - Fixed output - Emergency

#### Dimensions

C (mm)	102
Dia. (mm)	435

#### Line Drawing

