

Order Code: XCBHWPCBOHFS

16W - Circular Bulkhead with Opal Diffuser - IP65 - 4000K - Black Base - Microwave Sensor



Features

- Suitable for general interior or exterior use
- 20mm conduit side cable entries for wall or ceiling fix
- Up to 94 lumens per watt efficacy

Construction

- High quality polycarbonate construction
- Polycarbonate body
- White base or black base available
- Opal or prismatic diffuser available
- Integral emergency option available
- Supplied as standard with neutral white [4000K] LED



Technical Data

General		Electrical	
Luminaire Wattage (W)	16	Rated Input Current (A)	0.07
Weight (kg)	0.86	Power Factor (pf)	0.9
Operating Temperature (ta °C)	0 to 25	Input Voltage Range (VAC)	220-240
Light Output		Inrush Current Peak (A)	10
		Surge Protection (kV)	1
		Conductor Size (mm)	2.5
Lumens (lm)	1500	Terminal Type	3 pole piano key
Efficacy (lm/W)	94		
LED			
CCT (K)	4000		
CRI	80		
Macadam Ellipses	4		
Driver			
Driver Current (mA)	240		
Forward Voltage (V)	54-64		

Order Code: XCBHWPCBOHFS

16W - Circular Bulkhead with Opal Diffuser - IP65 - 4000K - Black Base - Microwave Sensor

Dimensions

C (mm)	85
Dia. (mm)	282

Line Drawing

