xcite LED Lighting

Data Sheet



0.07 0.85 220-240

2.5

4 pole screw down

Order Code: XCBHWPCWOM3HFS

16W - Circular Bulkhead with Opal Diffuser - IP65 - 3hrs Maintained Emergency - 4000K - White Base - Microwave Sensor Features



• Suitable for general interior or exterior use

- 20mm conduit side cable entries for wall or ceiling fix
- Up to 94 lumens per watt efficacy

Construction

- High quality polycarbonate construction
- Polycarbonate body
- White base or black base available
- Opal or prismatic diffuser available
- Integral emergency option available
- Supplied as standard with neutral white [4000K] LED















Technical Data

| i ecimicai Data | | |
|-------------------------------|---------|---------------------------|
| General | | Electrical |
| Luminaire Wattage (W) | 16 | Rated Input Current (A) |
| Weight (kg) | 1.18 | Power Factor (pf) |
| Operating Temperature (ta °C) | 5 to 25 | Input Voltage Range (VAC) |
| Light Output Lumens (Im) | | Inrush Current Peak (A) |
| | 1500 | Surge Protection (kV) |
| Efficacy (Im/W) | 94 | Conductor Size (mm) |
| LED | | Terminal Type |
| CCT (K) | 4000 | |
| CRI | 80 | |
| Macadam Elipses | 4 | |
| Emergency | | |
| Emergency Lumen Operating | 210 | |
| Emergency Wattage (W) | 2 | |
| | | |

xcite LED Lighting

Data Sheet



Order Code: XCBHWPCWOM3HFS

16W - Circular Bulkhead with Opal Diffuser - IP65 - 3hrs Maintained Emergency - 4000K - White Base - Microwave Sensor

Dimensions

| C (mm) | 85 |
|-----------|-----|
| Dia. (mm) | 282 |

Line Drawing

