xcite LED Lighting
Data Sheet

Order Code: XCBHWPSWOM3

16W - Square Bulkhead with Opal diffuser - IP65 - 3hrs Maintained Emergency - 4000K - White Base



Features

- Suitable for general interior or exterior use
- 20mm conduit side cable entries for wall or ceiling fix
- Up to 94 lumens per watt efficacy

Construction

- High quality polycarbonate construction
- Polycarbonate body
- White base or black base available
- Opal or prismatic diffuser available
- Integral emergency option available
- Supplied as standard with neutral white [4000K] LED

4000K | 50,000 HOURS | 3YRS WARRANTY | IP65 | IK08 | M3

Technical Data

General

Luminaire Wattage (W)	16
Weight (kg)	1.06
Operating Temperature (ta °C)	5 to 25

Light Output

Lumens (lm)	1500
Efficacy (lm/W)	94

LED

CCT (K)	4000
CRI	80
Macadam Elipses	4

Emergency

Emergency Lumen Operating	210
Emergency Wattage (W)	2

Electrical

Rated Input Current (A)	0.07
Power Factor (pf)	0.85
Input Voltage Range (VAC)	220-240
Inrush Current Peak (A)	10
Surge Protection (kV)	1
Conductor Size (mm)	2.5
Terminal Type	4 pole screw down

Technical
Stafford Park 12
Telford, Shropshire,
TF3 3BJ

T: +44 (0)1952 292441
E: sales@xciteledlighting.co.uk
W: www.xciteledlighting.co.uk

Order Code: XCBHWPSWOM3

16W - Square Bulkhead with Opal diffuser - IP65 - 3hrs Maintained Emergency - 4000K - White Base

Dimensions

Length (mm)	256
Width (mm)	256
Depth (mm)	93

Technical
Stafford Park 12
Telford, Shropshire,
TF3 3BJ

T: +44 (0)1952 292441
E: sales@xciteledlighting.co.uk
W: www.xciteledlighting.co.uk