xcite LED Lighting

Data Sheet



Order Code: XCBLAM3ST

XCITE BLADE ST XCBLA 2W - 6500K - Fixed output - Emergency Self-test



Features

- Ideal for retrofit of existing emergency fixtures
- Suitable for ceiling, wall or surface fixings
- 20mm conduit rear cable entries
- Supplied with flag pole mounting kit
- Multi purpose LED emergency drop light
- Supplied with LiFePO4 battery

Construction

- Operates in maintained and non-maintained mode
- Supplied with EURO 4 running man legend
- Integral auto self-test for reduced maintenance











Technical Data

General		Electrical	
Luminaire Wattage (W)	2	Rated Input Current (A)	0.04
Weight (kg)	0.79	Power Factor (pf)	0.2
Operating Temperature (ta °C)	5° to 25°	Input Voltage Range (VAC)	220 to 240
Driver Driver Current (mA)		Conductor Size (mm)	1.5
	135	Terminal Type	4 pole screw down
Forward Voltage (V)	2.64		



xcite LED Lighting

Data Sheet



Order Code: XCBLAM3ST

XCITE BLADE ST XCBLA 2W - 6500K - Fixed output - Emergency Self-test

Dimensions

A (mm)	344
B (mm)	237
C (mm)	42

