

**Order Code: XCBOLX1SGC**

X1 Bollard XCBOL - Grey - [3000K/4000K/5000K] + Wattage Switchable - Cone - Fixed output



**Features**

- CCT selectable via selector switch [3000K/4000K/5000K]
- Wattage selectable via 2-way dip switch [12W/16W/20W]
- Up to 103 lumens per watt efficacy
- Ground Mounting [J-BOLT KIT](#) [sold separately]

**Construction**

- Weatherproof IP65 construction
- Loop in/out mains connector
- Die-cast aluminium construction designed to resist corrosion and prevent rust, finished in black [RAL 9005]

**Technical Data**

**General**

Luminaire Wattage (W)	12W/16W/20W
Operating Temperature (ta °C)	-20 to +50

**Light Output**

Lumens (lm)	1100 to 1800
Efficacy (lm/W)	103

**LED**

CCT (K)	3000K/4000K/5000K
CRI	80
Macadam Elipses	5.4

**Driver**

Driver Current (mA)	285
Forward Voltage (V)	50 to 70

**Electrical**

Rated Input Current (A)	0.05 to 0.09
Power Factor (pf)	0.9 to 0.96
Input Voltage Range (VAC)	220 to 240
Inrush Current Peak (A)	11.13
Surge Protection (kV)	4
Terminal Type	3 Pole

### Order Code: XCBOLX1SGC

X1 Bollard XCBOL - Grey - [3000K/4000K/5000K] + Wattage Switchable - Cone - Fixed output

#### Dimensions

C (mm)	600
Dia. (mm)	120

#### Line Drawing

