

## Order Code: XCCDL3NWW

3W - Circular Under Cabinet Downlight - IP20 - 4000K - White



## Features

- LED circular under cabinet downlight
- Suitable for kitchen or wardrobe applications
- Can be surface or flush/recessed mounted
- Complete with 0.5m of mains, 2 core cable
- Up to 67 lumens per watt efficacy

## Construction

- Pressed steel body
- Frosted polycarbonate diffuser
- Integral driver circuitry with mains input
- Available in warm white [3000K] or neutral white [4000K]

Note: Please note dimensions relate to the 'surface' fitting [WITH TRIM]. The dimensions [WITHOUT TRIM] for recessed install are [Cut-out. 60mm] [Dia. 68mm] [C. 23mm]

## Technical Data

## General

Luminaire Wattage (W)	3
Weight (kg)	0.17
Operating Temperature (ta °C)	0 to 25

## Light Output

Lumens (lm)	200
Efficacy (lm/W)	67

## Electrical

Rated Input Current (A)	0.011
Power Factor (pf)	0.4
Input Voltage Range (VAC)	220-240
Surge Protection (kV)	2
Conductor Size (mm)	0.5
Terminal Type	Bare wire

## LED

CCT (K)	4000
CRI	80
Macadam Ellipses	3

**Order Code: XCCDL3NWW**

3W - Circular Under Cabinet Downlight - IP20 - 4000K - White

## Dimensions

C (mm)	23
Cut Out (mm)	68
Dia. (mm)	74

## Line Drawing

