xcite LED Lighting
Data Sheet

xcite ®
LED LIGHTING

Order Code: XCDRV75
75W - 12V LED Strip Driver Non-Dimmable

Features

- Short circuit and overload protection
- For use with single colour or RGB LED strip

Construction

- Constant voltage LED driver for use with xcite LED strip

LED POWER SUPPLY
Model:XCDRV50IP20

INPUT..............220-240V~
50/60Hz 0.4A
OUTPUT............12V⎓4.16A 50W
λ≥0.9 tc:85℃ ta:40℃ •tc

Constant Voltage
For LED module only
SELV

CE ☐ UKCA ⌂ IP20 MADE IN CHINA
2022. 05

30,000 HOURS | 3YRS WARRANTY | ☐ | IP20 | DALI DIMMABLE

Technical Data

General

Luminaire Wattage (W)	75
Weight (kg)	0.24
Operating Temperature (ta °C)	0 to 25

Electrical

Input Voltage Range (VAC)	220-240
Surge Protection (kV)	1

Technical
Stafford Park 12
Telford, Shropshire,
TF3 3BJ

T: +44 (0)1952 292441
E: sales@xciteledlighting.co.uk
W: www.xciteledlighting.co.uk

CE UKCA ☒

Generated on: 14/04/2026 7:11am
Produced by xcite LED Lighting

Order Code: XCDRV75

75W - 12V LED Strip Driver Non-Dimmable

Dimensions

A (mm)	170
B (mm)	56
C (mm)	30

Line Drawing

Technical
Stafford Park 12
Telford, Shropshire,
TF3 3BJ

T: +44 (0)1952 292441
E: sales@xciteledlighting.co.uk
W: www.xciteledlighting.co.uk

Generated on: 14/04/2026 7:11am
Produced by xcite LED Lighting