# xcite LED Lighting

## **Data Sheet**



0.03

1.5

220 to 240

3 pole screw down

Order Code: XCEDLA1NM3CST

XCITE EM DOWNLIGHT ST XCEDLA - 6500K - Fixed output - non-maintainted Emergency Self-test Corridor function



#### **Features**

- Suitable for open areas and escape routes
- · Virtually service free emergency lighting
- · Easy to install with simple connection wiring
- Supplied with LiFePO4 battery

### Construction

- Polycarbonate body
- Very low energy consumption 1W
- Separate high quality LED driver
- Operates in non-maintained mode
- Internal mains connection
- Integral auto self-test for reduced maintenance



#### **Technical Data**

General			Electrical
Luminaire Wattage (W)	1	Rated Input Current (A)	
Weight (kg)	0.36	Power Factor (pf)	
Operating Temperature (ta °C)	5° to 25°	Input Voltage Range (VAC)	
LED		Conductor Size (mm)	
LED CRI	70	Terminal Type	
Driver			
Driver Current (mA)	350		
Forward Voltage (V)	3.1		
Emergency			
Emergency Lumen Operating	140		
Emergency Wattage (W)	1		

# xcite LED Lighting

# Data Sheet



### Order Code: XCEDLA1NM3CST

XCITE EM DOWNLIGHT ST XCEDLA - 6500K - Fixed output - non-maintainted Emergency Self-test Corridor function

#### **Dimensions**

C (mm)	57
Cut Out (mm)	50
Dia. (mm)	60

### Line Drawing



