# xcite LED Lighting

## **Data Sheet**



Order Code: XCEDLA1NM3ST

XCITE EM DOWNLIGHT ST XCEDLA - 6500K - Fixed output - non-maintainted Emergency Self-test



#### **Features**

- Suitable for open areas and escape routes
- Virtually service free emergency lighting
- · Easy to install with simple connection wiring
- Supplied with LiFePO4 battery

#### Construction

- Polycarbonate body
- Very low energy consumption 1W
- Separate high quality LED driver
- Operates in non-maintained mode
- Internal mains connection
- Integral auto self-test for reduced maintenance



### **Technical Data**

General		Electrical	
Luminaire Wattage (W)	1	Rated Input Current (A)	0.03
Weight (kg)	0.36	Power Factor (pf)	0.04
Operating Temperature (ta °C)	5° to 25°	Input Voltage Range (VAC)	220 to 240
LED		Conductor Size (mm)	1.5
CRI	70	Terminal Type	3 pole screw down
Driver			
Driver Current (mA)	350		
Forward Voltage (V)	3.1		
Emergency			
Emergency Lumen Operating	140		
Emergency Wattage (W)	1		



# xcite LED Lighting

# Data Sheet



### Order Code: XCEDLA1NM3ST

XCITE EM DOWNLIGHT ST XCEDLA - 6500K - Fixed output - non-maintainted Emergency Self-test

#### **Dimensions**

C (mm)	57
Cut Out (mm)	50
Dia. (mm)	60

### Line Drawing



