

## Order Code: XCEMBANM3ST

XCITE EM BULKHEAD ST XCEMBA 1W - 6500K - Fixed output - non-maintained Emergency Self-test

## Features



- Suitable for open areas and escape routes
- 20mm conduit side and rear cable entries for wall or ceiling fix
- Semi recessed bezel available
- Reduced maintenance and high performance
- Supplied with LiFePO4 battery

## Construction

- Polycarbonate body and diffuser
- Maintained or non-maintained available
- Supplied with self adhesive universal legend
- Supplied as standard with daylight [6500K] LED
- Integral auto self-test for reduced maintenance, includes a disable function



## Technical Data

## General

|                               |           |
|-------------------------------|-----------|
| Luminaire Wattage (W)         | 1         |
| Weight (kg)                   | 0.51      |
| Operating Temperature (ta °C) | 5° to 25° |

## LED

|                  |     |
|------------------|-----|
| CRI              | 70  |
| Macadam Ellipses | 2.1 |

## Driver

|                     |     |
|---------------------|-----|
| Driver Current (mA) | 360 |
| Forward Voltage (V) | 3.4 |

## Emergency

|                           |     |
|---------------------------|-----|
| Emergency Lumen Operating | 190 |
| Emergency Wattage (W)     | 1   |

## Electrical

|                           |            |
|---------------------------|------------|
| Rated Input Current (A)   | 0.03       |
| Power Factor (pf)         | 0.17       |
| Input Voltage Range (VAC) | 220 to 240 |
| Conductor Size (mm)       | 1.5        |

3 pole piano key

**Order Code: XCEMBANM3ST**

XCITE EM BULKHEAD ST XCEMBA 1W - 6500K - Fixed output - non-maintained Emergency Self-test

## Dimensions

|        |     |
|--------|-----|
| A (mm) | 352 |
| B (mm) | 110 |
| C (mm) | 65  |

## Line Drawing

