xcite LED Lighting
Data Sheet

Order Code: XCEMBNM3

1W - Emergency Bulkhead - 3hrs Non-Maintained Emergency



Features

- Suitable for open areas and escape routes
- 20mm conduit side and rear cable entries for wall or ceiling fix
- Semi recessed bezel available
- Reduced maintenance and high performance
- Polycarbonate body and diffuser

Construction

- Maintained or non-maintained available
- Supplied with self adhesive universal EURO 4 legend
- Supplied as standard with daylight [6500K] LED

6500K | 50,000 HOURS | 3YRS WARRANTY | IP65 | IK06 | M3 | NM3

Technical Data

General

Luminaire Wattage (W)	1
Weight (kg)	0.55
Operating Temperature (ta °C)	5 to 25

Light Output

Lumens (lm)	150

LED

CCT (K)	6500
CRI	70

Emergency

Emergency Lumen Operating	150
Emergency Wattage (W)	1

Electrical

Rated Input Current (A)	0.031
Power Factor (pf)	0.17
Input Voltage Range (VAC)	220-240
Conductor Size (mm)	1.5
Terminal Type	3 pole piano key

Technical
Stafford Park 12
Telford, Shropshire,
TF3 3BJ

T: +44 (0)1952 292441
E: sales@xciteledlighting.co.uk
W: www.xciteledlighting.co.uk

Order Code: XCEMBNM3

1W - Emergency Bulkhead - 3hrs Non-Maintained Emergency

Dimensions

Length (mm)	352
Width (mm)	110
Depth (mm)	65

Technical
Stafford Park 12
Telford, Shropshire,
TF3 3BJ

T: +44 (0)1952 292441
E: sales@xciteledlighting.co.uk
W: www.xciteledlighting.co.uk