# xcite LED Lighting

## **Data Sheet**



Order Code: XCEMBNM3

1W - Emergency Bulkhead - 3hrs Non-Maintained Emergency



### **Features**

- Suitable for open areas and escape routes
- 20mm conduit side and rear cable entries for wall or ceiling fix
- Semi recessed bezel available
- Reduced maintenance and high performance
- Polycarbonate body and diffuser

#### Construction

- Maintained or non-maintained available
- Supplied with self adhesive universal EURO 4 legend
- Supplied as standard with daylight [6500K] LED















### **Technical Data**

General		Electrical
Luminaire Wattage (W)	1	Rated Input Current (A)
Weight (kg)	0.55	Power Factor (pf)
Operating Temperature (ta °C)	5 to 25	Input Voltage Range (VAC)
Light Output  Lumens (Im)		Conductor Size (mm)
	150	Terminal Type
LED		
CCT (K)	6500	
CRI	70	
Emergency		
Emergency Lumen Operating	150	
Emergency Wattage (W)	1	



0.031 0.17 220-240 1.5

3 pole piano key

# xcite LED Lighting

# **Data Sheet**



## Order Code: XCEMBNM3

1W - Emergency Bulkhead - 3hrs Non-Maintained Emergency

### **Dimensions**

A (mm)	352
B (mm)	110
C (mm)	65

### Line Drawing



