

Order Code: XCEMBNM3ST
1W - Fixed output - Non-maintained Emergency Self-test - 6500K



Features

- Suitable for open areas and escape routes
- 20mm conduit side and rear cable entries for wall or ceiling fix
- Reduced maintenance and high performance
- Semi recessed bezel available

Construction

- Polycarbonate body and diffuser
- Maintained or non-maintained available
- Supplied as standard with daylight [6500K] LED
- Integral auto self-test for reduced maintenance



Technical Data

General		Electrical	
Luminaire Wattage (W)	1	Rated Input Current (A)	0.031
Weight (kg)	0.55	Power Factor (pf)	0.17
Operating Temperature (ta °C)	5 to 25	Input Voltage Range (VAC)	220-240
Light Output		Conductor Size (mm)	1.5
Lumens (lm)	140	Terminal Type	3 pole piano key
LED			
CCT (K)	6500		
CRI	70		
Driver			
Forward Voltage (V)	3.4		
Emergency			
Emergency Lumen Operating	140		
Emergency Wattage (W)	1		

Order Code: XCEMBNM3ST
1W - Fixed output - Non-maintained Emergency Self-test - 6500K

Dimensions

A (mm)	352
B (mm)	110
C (mm)	65

Line Drawing

