

Order Code: XCFC10CT

10W - Floodlight - CCTK Selector - [3000K/4000K/6000K]

**Features**

- Ideal for retrofit of existing halogen fixtures, lighting buildings, car parks or doorways
- CCT [3000K/4000K/6000K] adjustable via 3-way selector switch
- Available with high performance PIR or microwave detector
- Available in 4 different outputs
- High quality toughened safety glass
- Supplied with stirrup and 1m of flex for column, bracket or surface fix
- Up to 100 lumens per watt efficacy

Construction

- Die-cast aluminium body finished with black marine grade paint finish
- Weatherproof IP65 construction
- CRI: Ra>80

Technical Data**General**

Luminaire Wattage (W)	10
Weight (kg)	0.55
Operating Temperature (ta °C)	-20 to 40

Electrical

Rated Input Current (A)	0.0422
Power Factor (pf)	0.9
Input Voltage Range (VAC)	220-240
Terminal Type	3 pole screw down

Light Output

Lumens (lm)	1000
Efficacy (lm/W)	100

LED

CCT (K)	TRI-COLOUR
CRI	>80
Macadam Ellipses	<5

Order Code: XCFC10CT

10W - Floodlight - CCTK Selector - [3000K/4000K/6000K]

Dimensions

A (mm)	164
B (mm)	129
C (mm)	39

Line Drawing

