xcite LED Lighting

Data Sheet

EXCITE

Order Code: XCFC150NW 150W - High Output Floodlight - 4000K



Features

- Suitable for exterior building and feature lighting
- Supplied with stirrup and 1m of flex for column, bracket or surface fix
- High quality toughened safety glass

Construction

- Die-cast aluminium body finished with black marine grade paint finish
- Weatherproof IP65 construction
- Breather gland for reducing condensation
- Supplied as standard with neutral white [4000K] LED













Technical Data

General	
Luminaire Wattage (W)	150
Weight (kg)	2.38
Operating Temperature (ta °C)	-20 to 25
Light Output	-
Lumens (Im)	16000
Efficacy (lm/W)	107
LED	
CCT (K)	4000
CRI	>80
Macadam Elipses	4
Driver	
Driver Current (mA)	520
Forward Voltage (V)	230

Electrical	
Dated land Courset (A)	0.70
Rated Input Current (A)	0.73
Power Factor (pf)	0.9
Input Voltage Range (VAC)	220-240
Terminal Type	3-CORE FLEX



xcite LED Lighting

Data Sheet




Order Code: XCFC150NW 150W - High Output Floodlight - 4000K

Dimensions

A (mm)	385
B (mm)	280
C (mm)	40

Line Drawing





С