# xcite LED Lighting

## **Data Sheet**

**EXCITE** 

Order Code: XCFC200NW 200W - High Output Floodlight - 4000K



### **Features**

- Suitable for exterior building and feature lighting
- Supplied with stirrup and 1m of flex for column, bracket or surface fix
- High quality toughened safety glass

### Construction

- Die-cast aluminium body finished with black marine grade paint finish
- Weatherproof IP65 construction
- Breather gland for reducing condensation
- Supplied as standard with neutral white [4000K] LED













## Technical Data

General	
Luminaire Wattage (W)	200
Weight (kg)	2 25
Operating Temperature (ta °C)	-20 to 25
Light Output	
Lumens (lm)	20000
Efficacy (lm/W)	100
LED	
CCT (K)	4000
CRI	>80
Macadam Elipses	4
Driver	
Driver Current (mA)	670
Forward Voltage (V)	230

Electrical	
Rated Input Current (A)	0.97
Power Factor (pf)	0.9
Input Voltage Range (VAC)	220-240
Terminal Type	3-CORE FLEX



# xcite LED Lighting

## **Data Sheet**




Order Code: XCFC200NW 200W - High Output Floodlight - 4000K

### **Dimensions**

A (mm)	380
B (mm)	300
C (mm)	40

## Line Drawing





С