

## Order Code: XCFC20CT

20W - Floodlight - CCTK Selector [3000K/4000K/6000K]



## Features

- Ideal for retrofit of existing halogen fixtures, lighting buildings, car parks or doorways
- CCT [3000K/4000K/6000K] adjustable via 3-way selector switch
- Available in 4 different outputs
- Available with high performance PIR or microwave detector
- High quality toughened safety glass
- Supplied with stirrup and 1m of flex for column, bracket or surface fix
- Up to 100 lumens per watt efficacy

## Construction

- Die-cast aluminium body finished with black marine grade paint finish
- Weatherproof IP65 construction
- CRI: Ra>80

## Technical Data

## General

Luminaire Wattage (W)	20
Weight (kg)	0.82
Operating Temperature (ta °C)	-20 to 40

## Electrical

Rated Input Current (A)	0.0839
Power Factor (pf)	0.9
Input Voltage Range (VAC)	220-240
Terminal Type	3 pole screw down

## Light Output

Lumens (lm)	2000
Efficacy (lm/W)	100

## LED

CCT (K)	TRI-COLOUR
CRI	>80
Macadam Ellipses	<5

**Order Code: XCFC20CT**

20W - Floodlight - CCTK Selector [3000K/4000K/6000K]

## Dimensions

A (mm)	208
B (mm)	159
C (mm)	39

## Line Drawing

