

**Order Code: XCFRA7CT**

7W - Fire Rated Recessed Downlight - IP65 - CCTK Selector [3000K/4000K/6000K]

**Features**

- Ideal for retrofit of existing halogen downlight fixtures
- Suitable for domestic applications
- CCT [3000K/4000K/6000K] adjustable via 3-way selector switch
- Available in 5 different coloured bezels and 2 sizes [not included]
- Dimmable as standard
- Convert to larger sized cut outs with the [Conversion Plates](#)
- 30, 60 & 90 minute fire rating with solid timber joists
- 30 minute fire rating with Staircraft I-Joist [\[Compatibility Matrix\]](#)
- Up to 100 lumens per watt efficacy

**Construction**

- Loop in/out mains connections with easy-fit connector

**Technical Data****General**

Luminaire Wattage (W)	7
Operating Temperature (ta °C)	0 to 25

**Light Output**

Lumens (lm)	600-700
Efficacy (lm/W)	100

**LED**

CCT (K)	TRI-COLOUR
CRI	80
Macadam Ellipses	4

**Driver**

Driver Current (mA)	19
Forward Voltage (V)	260

**Electrical**

Rated Input Current (A)	0.03
Input Voltage Range (VAC)	220-240
Inrush Current Peak (A)	1.04
Surge Protection (kV)	1
Conductor Size (mm)	2.5
Terminal Type	3-POLE GRIP-WIRE

**Order Code: XCFRA7CT**

7W - Fire Rated Recessed Downlight - IP65 - CCTK Selector [3000K/4000K/6000K]

## Dimensions

C (mm)	60
Cut Out (mm)	62
Dia. (mm)	75

## Line Drawing

