

**Order Code:** XCLGP6630CW

30W - Recessed Low Glare Panel - 600m x 600m - 5000K



### Features

- Backlit recessed module
- More consistent and uniform appearance than traditional edge-lit panels or downlights
- Compatible with [Panel Frame](#) and [Surface Panel Frame](#)
- 3 hours emergency maintained with compatible conversion box [Emergency Kit](#)
- Up to 100 lumens per watt efficacy

### Construction

- Extruded aluminium frame
- Plug and play driver
- Supplied in warm white [3000K], neutral white [4000K], cool white [5000K] or daylight [6000K]



### Technical Data

#### General

|                               |         |
|-------------------------------|---------|
| Luminaire Wattage (W)         | 30      |
| Weight (kg)                   | 1.64    |
| Operating Temperature (ta °C) | 0 to 25 |

#### Light Output

|                 |      |
|-----------------|------|
| Lumens (lm)     | 3000 |
| Efficacy (lm/W) | 100  |

#### LED

|                 |      |
|-----------------|------|
| CCT (K)         | 5000 |
| CRI             | 80   |
| Macadam Elipses | 4    |

#### Driver

|                     |          |
|---------------------|----------|
| Driver Current (mA) | 750      |
| Forward Voltage (V) | 24 to 42 |

#### Electrical

|                           |                  |
|---------------------------|------------------|
| Rated Input Current (A)   | 0.13             |
| Power Factor (pf)         | 0.9              |
| Input Voltage Range (VAC) | 220-240          |
| Inrush Current Peak (A)   | 40               |
| Surge Protection (kV)     | 1                |
| Conductor Size (mm)       | 1.5              |
| Terminal Type             | 2 pole grip wire |

Order Code: XCLGP6630CW

30W - Recessed Low Glare Panel - 600m x 600m - 5000K

Dimensions

|        |     |
|--------|-----|
| A (mm) | 595 |
| B (mm) | 595 |
| C (mm) | 35  |

Line Drawing

