

Order Code: XCLGP66X1

X1 LG PANEL - White- Wattage Selectable - Dimmable - CCT [4000K/5000K/6000K] - Micro-prism diffuser - Fixed output

Features

- CCT selectable via selector switch [4000K/5000K/6000K]
- Wattage selectable via selector switch [17W/19W/21W/23W/25W/27W]
- Up to 141 lumens per watt efficacy
- More consistent and uniform appearance than traditional edge-lit panels or downlights
- 3 hours emergency maintained with compatible conversion box [Emergency Kit](#)
- Compatible with [Panel Frame](#) and [Surface Panel Frame](#)

Construction

- Low glare micro prismatic polycarbonate Tp[a] rated diffuser
- Non-dimmable variant wired via Loop in/out 3-pole plug & play connector
- Extruded aluminium frame

Installation Notes

Wired via 3-pole terminal connection inside main body



Technical Data

General		Electrical	
Luminaire Wattage (W)	17W/19W/21W/23W/25W/27W	Rated Input Current (A)	0.8 to 0.12
Weight (kg)	1.79	Power Factor (pf)	0.91 to 0.95
Operating Temperature (ta °C)	5° to 25°	Input Voltage Range (VAC)	220 to 240
Light Output		Inrush Current Peak (A)	22.1
Lumens (lm)	2300 to 3500	Surge Protection (kV)	1kV
Efficacy (lm/W)	141	Conductor Size (mm)	0.5 to 2.5
LED		Terminal Type	2 Push Terminal
CCT (K)	4000K/5000K/6000K		
CRI	80		
Macadam Ellipses	3.1 to 13.1		
Driver			
Driver Current (mA)	450 - 500 / 550 - 600 / 650 - 700		
Forward Voltage (V)	32.4 to 34.2		

Order Code: XCLGP66X1

X1 LG PANEL - White- Wattage Selectable - Dimmable - CCT [4000K/5000K/6000K] - Micro-prism diffuser - Fixed output

Dimensions

A (mm)	595
B (mm)	595
B (mm)	35

Line Drawing

