

**Order Code: XCNC14HENW**

32W - 1200mm Non Corrosive Polycarbonate Luminaire - IP65 - 4000K



**Features**

- Ideal for replacement of linear fluorescent fixtures
- Available in 3 lengths
- Microwave movement sensor available
- Up to 156 lumens per watt efficacy

**Construction**

- Grey polycarbonate body
- Supplied with opal diffuser
- Integral emergency option available
- Stainless steel fixing clips
- Supplied with neutral white [4000K]
- CRI: Ra>80



Note: This luminaire is not suitable for all chemical environments, please contact us for advice if this luminaire may be exposed to, oil, grease, solvents, acids, alkaline or any similar chemicals.

**Technical Data**

| General                       |           | Electrical                |                  |
|-------------------------------|-----------|---------------------------|------------------|
| Luminaire Wattage (W)         | 32        | Rated Input Current (A)   | 0.14             |
| Weight (kg)                   | 1.83      | Power Factor (pf)         | 0.98             |
| Operating Temperature (ta °C) | -20 to 25 | Input Voltage Range (VAC) | 198-264          |
|                               |           | Inrush Current Peak (A)   | 20.02            |
|                               |           | Conductor Size (mm)       | 2.5              |
|                               |           | Terminal Type             | 3 pole piano key |
| Light Output                  |           |                           |                  |
| Lumens (lm)                   | 5000      |                           |                  |
| Efficacy (lm/W)               | 156       |                           |                  |
| LED                           |           |                           |                  |
| CCT (K)                       | 4000      |                           |                  |
| CRI                           | 80        |                           |                  |
| Macadam Ellipses              | 2         |                           |                  |
| Driver                        |           |                           |                  |
| Driver Current (mA)           | 700mA     |                           |                  |
| Forward Voltage (V)           | 24-42     |                           |                  |

**Order Code:** XCNC14HENW

32W - 1200mm Non Corrosive Polycarbonate Luminaire - IP65 - 4000K

Dimensions

|        |      |
|--------|------|
| A (mm) | 1260 |
| B (mm) | 98   |
| C (mm) | 93   |

Line Drawing

