

Order Code: XCNC14HENWHFS

32W - 1200mm Non Corrosive Polycarbonate Luminaire - IP65 - Microwave Sensor - 4000K

**Features**

- Ideal for replacement of linear fluorescent fixtures
- Available in 3 lengths
- Microwave movement sensor available
- Up to 156 lumens per watt efficacy

Construction

- Grey polycarbonate body
- Supplied with opal diffuser
- Integral emergency option available
- Stainless steel fixing clips
- CRI: Ra>80
- Supplied with neutral white [4000K]

Note: This luminaire is not suitable for all chemical environments, please contact us for advice if this luminaire may be exposed to, oil, grease, solvents, acids, alkaline or any similar chemicals.

Technical Data**General**

Luminaire Wattage (W)	32
Weight (kg)	1.93
Operating Temperature (ta °C)	-20 to 25

Light Output

Lumens (lm)	5000
Efficacy (lm/W)	156

Electrical

Rated Input Current (A)	0.14
Power Factor (pf)	0.98
Input Voltage Range (VAC)	198-264
Inrush Current Peak (A)	20.02
Conductor Size (mm)	2.5
Terminal Type	3 pole piano key

LED

CCT (K)	4000
CRI	80
Macadam Ellipses	2

Driver

Driver Current (mA)	700mA
Forward Voltage (V)	24-42

Order Code: XCNC14HENWHFS

32W - 1200mm Non Corrosive Polycarbonate Luminaires - IP65 - Microwave Sensor - 4000K

Dimensions

A (mm)	1260
B (mm)	98
C (mm)	93

Line Drawing

