

Order Code: XCNC14HENWHFSM3

32W - 1200mm Non Corrosive Polycarbonate Luminaire - IP65 - Microwave Sensor - 3hrs Maintained Emergency - 4000K



Features

- Ideal for replacement of linear fluorescent fixtures
- Available in 3 lengths
- Microwave movement sensor available
- Up to 156 lumens per watt efficacy

Construction

- Grey polycarbonate body
- Supplied with opal diffuser
- Integral emergency option available
- Stainless steel fixing clips
- CRI: Ra>80
- Supplied with neutral white [4000K]



Note: This luminaire is not suitable for all chemical environments, please contact us for advice if this luminaire may be exposed to, oil, grease, solvents, acids, alkaline or any similar chemicals.

Technical Data

General		Electrical	
Luminaire Wattage (W)	32	Rated Input Current (A)	0.14
Weight (kg)	1.93	Power Factor (pf)	0.98
Operating Temperature (ta °C)	5 to 25	Input Voltage Range (VAC)	198-264
Light Output		Inrush Current Peak (A)	20.02
		Lumens (lm)	5000
		Conductor Size (mm)	2.5
Efficacy (lm/W)	156	Terminal Type	4 pole piano key
LED			
CCT (K)	4000		
CRI	80		
Macadam Ellipses	2		
Driver			
Driver Current (mA)	700mA		
Forward Voltage (V)	24-42		
Emergency			
Emergency Lumen Operating	160		
Emergency Wattage (W)	1		

Order Code: XCNC14HENWHFSM3

32W - 1200mm Non Corrosive Polycarbonate Luminaire - IP65 - Microwave Sensor - 3hrs Maintained Emergency - 4000K

Dimensions

A (mm)	1260
B (mm)	98
C (mm)	93

Line Drawing

