

Order Code: XCNC15HENWHFS

51W - 1500mm Non Corrosive Polycarbonate Luminaire - IP65 - Microwave Sensor - 4000K



Features

- Ideal for replacement of linear fluorescent fixtures
- Available in 3 lengths
- Microwave movement sensor available
- Up to 137 lumens per watt efficacy

Construction

- Grey polycarbonate body
- Supplied with opal diffuser
- Integral emergency option available
- Stainless steel fixing clips
- CRI: Ra>80
- Supplied with neutral white [4000K]



Note: This luminaire is not suitable for all chemical environments, please contact us for advice if this luminaire may be exposed to, oil, grease, solvents, acids, alkaline or any similar chemicals.

Technical Data

| General | | Electrical | |
|-------------------------------|-----------|---------------------------|------------------|
| Luminaire Wattage (W) | 51 | Rated Input Current (A) | 0.23 |
| Weight (kg) | 2.34 | Power Factor (pf) | 0.97 |
| Operating Temperature (ta °C) | -20 to 25 | Input Voltage Range (VAC) | 198-264 |
| | | Inrush Current Peak (A) | 33.1 |
| | | Conductor Size (mm) | 2.5 |
| | | Terminal Type | 3 pole piano key |
| Light Output | | | |
| Lumens (lm) | 7000 | | |
| Efficacy (lm/W) | 137 | | |
| LED | | | |
| CCT (K) | 4000 | | |
| CRI | 80 | | |
| Macadam Ellipses | 2 | | |
| Driver | | | |
| Driver Current (mA) | 1150mA | | |
| Forward Voltage (V) | 28-52 | | |

Order Code: XCNC15HENWHFS

51W - 1500mm Non Corrosive Polycarbonate Luminaire - IP65 - Microwave Sensor - 4000K

Dimensions

| | |
|--------|------|
| A (mm) | 1560 |
| B (mm) | 98 |
| C (mm) | 93 |

Line Drawing

