xcite LED Lighting

Data Sheet



Order Code: XCNC15HENWHFS

51W - 1500mm Non Corrosive Polycarbonate Luminaire - IP65 - Microwave Sensor - 4000K



















Features

- · Ideal for replacement of linear fluorescent fixtures
- · Available in 3 lengths
- Microwave movement sensor available
- Up to 137 lumens per watt efficacy

Construction

- Grey polycarbonate body
- Supplied with opal diffuser
- Integral emergency option available
- Stainless steel fixing clips
- CRI: Ra>80
- Supplied with neutral white [4000K]

Note: This luminaire is not suitable for all chemical environments, please contact us for advice if this luminaire may be exposed to, oil, grease, solvents, acids, alkaline or any similar chemicals.

Technical Data

General		Electrica	ı
Luminaire Wattage (W)	51	Rated Input Current (A)	0.23
Weight (kg)	2.34	Power Factor (pf)	0.97
Operating Temperature (ta °C)	-20 to 25	Input Voltage Range (VAC)	198-264
Light Output Lumens (Im)		Inrush Current Peak (A)	33.1
	7000	Conductor Size (mm)	2.5
Efficacy (lm/W)	137	Terminal Type	3 pole piano key
LED			
CCT (K)	4000		
CRI	80		
Macadam Elipses	2		
Driver			
Driver Current (mA)	1150mA		
Forward Voltage (V)	28-52		



xcite LED Lighting

Data Sheet



Order Code: XCNC15HENWHFS

51W - 1500mm Non Corrosive Polycarbonate Luminaire - IP65 - Microwave Sensor - 4000K

Dimensions

A (mm)	1560
B (mm)	98
C (mm)	93

Line Drawing





