

Order Code: XCNC15HENWM3

51W - 1500mm Non Corrosive Polycarbonate Luminaire - IP65 - 3hrs Maintained Emergency - 4000K

Features

- Ideal for replacement of linear fluorescent fixtures
- Available in 3 lengths
- Microwave movement sensor available
- Up to 137 lumens per watt efficacy

Construction

- Grey polycarbonate body
- Supplied with opal diffuser
- Integral emergency option available
- Stainless steel fixing clips
- CRI: Ra>80
- Supplied with neutral white [4000K]

Note: This luminaire is not suitable for all chemical environments, please contact us for advice if this luminaire may be exposed to, oil, grease, solvents, acids, alkaline or any similar chemicals.

Technical Data**General**

Luminaire Wattage (W)	51
Weight (kg)	2.24
Operating Temperature (ta °C)	5 to 25

Light Output

Lumens (lm)	7000
Efficacy (lm/W)	137

Electrical

Rated Input Current (A)	0.23
Power Factor (pf)	0.97
Input Voltage Range (VAC)	198-264
Inrush Current Peak (A)	33.1
Conductor Size (mm)	2.5
Terminal Type	4 pole piano key

LED

CCT (K)	4000
CRI	80
Macadam Ellipses	2

Driver

Driver Current (mA)	1150mA
Forward Voltage (V)	28-52

Emergency

Emergency Lumen Operating	160
Emergency Wattage (W)	1

Order Code: XCNC15HENWM3

51W - 1500mm Non Corrosive Polycarbonate Luminaires - IP65 - 3hrs Maintained Emergency - 4000K

Dimensions

A (mm)	1560
B (mm)	98
C (mm)	93

Line Drawing

