

Order Code: XCNC15NW
32W - 1500mm Non Corrosive Polycarbonate Luminaire - IP65 - 4000K



- Features
- Ideal for replacement of linear fluorescent fixtures
 - Available in 3 lengths
 - Microwave movement sensor available
 - Up to 144 lumens per watt efficacy
- Construction
- Grey polycarbonate body
 - Supplied with opal diffuser
 - Integral emergency option available
 - Stainless steel fixing clips
 - CRI: Ra>80
 - Supplied with neutral white [4000K]

Note: This luminaire is not suitable for all chemical environments, please contact us for advice if this luminaire may be exposed to, oil, grease, solvents, acids, alkaline or any similar chemicals.

Technical Data

General		Electrical	
Luminaire Wattage (W)	32	Rated Input Current (A)	0.1
Weight (kg)	2.24	Power Factor (pf)	0.98
Operating Temperature (ta °C)	-20 to 25	Input Voltage Range (VAC)	198-264
Light Output		Inrush Current Peak (A)	20.02
Lumens (lm)	4300	Conductor Size (mm)	2.5
Efficacy (lm/W)	144	Terminal Type	3 pole piano key
LED			
CCT (K)	4000		
CRI	80		
Macadam Ellipses	3		
Driver			
Driver Current (mA)	700mA		
Forward Voltage (V)	24-42		

Order Code: XCNC15NW
32W - 1500mm Non Corrosive Polycarbonate Luminaire - IP65 - 4000K

Dimensions

A (mm)	1560
B (mm)	98
C (mm)	93

Line Drawing

