## xcite LED Lighting

### **Data Sheet**



### Order Code: XCNC15NWHFS

32W - 1500mm Non Corrosive Polycarbonate Luminaire - IP65 - Microwave Sensor - 4000K



















#### **Features**

- · Ideal for replacement of linear fluorescent fixtures
- · Available in 3 lengths
- Microwave movement sensor available
- Up to 144 lumens per watt efficacy

### Construction

- Grey polycarbonate body
- Supplied with opal diffuser
- Integral emergency option available
- Stainless steel fixing clips
- CRI: Ra>80
- Supplied with neutral white [4000K]

Note: This luminaire is not suitable for all chemical environments, please contact us for advice if this luminaire may be exposed to, oil, grease, solvents, acids, alkaline or any similar chemicals.

### **Technical Data**

General		Electrical	
Luminaire Wattage (W)	32	Rated Input Current (A)	0.1
Weight (kg)	2.34	Power Factor (pf)	0.98
Operating Temperature (ta °C)	-20 to 25	Input Voltage Range (VAC)	198-264
Light Output Lumens (Im)		Inrush Current Peak (A)	20.02
	4300	Conductor Size (mm)	2.5
Efficacy (lm/W)	144	Terminal Type	3 pole piano key
LED			
CCT (K)	4000		
CRI	80		
Macadam Elipses	3		
Driver			
Driver Current (mA)	700mA		
Forward Voltage (V)	24-42		



# xcite LED Lighting

### **Data Sheet**



### Order Code: XCNC15NWHFS

32W - 1500mm Non Corrosive Polycarbonate Luminaire - IP65 - Microwave Sensor - 4000K

### **Dimensions**

A (mm)	1560
B (mm)	98
C (mm)	93

### Line Drawing



