xcite LED Lighting

Data Sheet



0.28 0.98 198-264 33.1 2.5

3 pole piano key

Order Code: XCNC16HENWHFS

63W - 1800mm Non Corrosive Polycarbonate Luminaire - IP65 - Microwave Sensor - 4000K

Features

- · Ideal for replacement of linear fluorescent fixtures
- · Available in 3 lengths
- Microwave movement sensor available
- Up to 140 lumens per watt efficacy

Construction

- Grey polycarbonate body
- Supplied with opal diffuser
- Integral emergency option available
- Stainless steel fixing clips
- CRI: Ra>80
- Supplied with neutral white [4000K]

Note: This luminaire is not suitable for all chemical environments, please contact us for advice if this luminaire may be exposed to, oil, grease, solvents, acids, alkaline or any similar chemicals.















Technical Data

General		Electrical
Luminaire Wattage (W)	63	Rated Input Current (A)
Weight (kg)	3.07	Power Factor (pf)
Operating Temperature (ta °C)	-20 to 25	Input Voltage Range (VAC)
Light Outpu	ı+	Inrush Current Peak (A)
Light Outpu Lumens (Im)	ut 8800	Conductor Size (mm)
Efficacy (Im/W)	140	Terminal Type
LED		
CCT (K)	4000	
CRI	80	
Macadam Elipses	3	
Driver		
Driver Current (mA)	1400mA	
Forward Voltage (V)	24-42	

xcite LED Lighting

Data Sheet



Order Code: XCNC16HENWHFS

63W - 1800mm Non Corrosive Polycarbonate Luminaire - IP65 - Microwave Sensor - 4000K

Dimensions

A (mm)	1830
B (mm)	100
C (mm)	101

Line Drawing





