

Order Code: XCNC16HENWHFS
63W - 1800mm Non Corrosive Polycarbonate Luminaire - IP65 - Microwave Sensor - 4000K



Features

- Ideal for replacement of linear fluorescent fixtures
- Available in 3 lengths
- Microwave movement sensor available
- Up to 140 lumens per watt efficacy

Construction

- Grey polycarbonate body
- Supplied with opal diffuser
- Integral emergency option available
- Stainless steel fixing clips
- CRI: Ra>80
- Supplied with neutral white [4000K]

Note: This luminaire is not suitable for all chemical environments, please contact us for advice if this luminaire may be exposed to, oil, grease, solvents, acids, alkaline or any similar chemicals.



Technical Data

General		Electrical	
Luminaire Wattage (W)	63	Rated Input Current (A)	0.28
Weight (kg)	3.07	Power Factor (pf)	0.98
Operating Temperature (ta °C)	-20 to 25	Input Voltage Range (VAC)	198-264
Light Output		Inrush Current Peak (A)	33.1
Lumens (lm)	8800	Conductor Size (mm)	2.5
Efficacy (lm/W)	140	Terminal Type	3 pole piano key
LED			
CCT (K)	4000		
CRI	80		
Macadam Elipses	3		
Driver			
Driver Current (mA)	1400mA		
Forward Voltage (V)	24-42		

Order Code: XCNC16HENWHFS
63W - 1800mm Non Corrosive Polycarbonate Luminaire - IP65 - Microwave Sensor - 4000K

Dimensions

A (mm)	1830
B (mm)	100
C (mm)	101

Line Drawing

