# xcite LED Lighting

## **Data Sheet**



### Order Code: XCNC16HENWM3

63W - 1800mm Non Corrosive Polycarbonate Luminaire - IP65 - 3hrs Maintained Emergency - 4000K

#### **Features**

- · Ideal for replacement of linear fluorescent fixtures
- · Available in 3 lengths
- Microwave movement sensor available
- Up to 140 lumens per watt efficacy

#### Construction

- Grey polycarbonate body
- Supplied with opal diffuser
- Integral emergency option available
- Stainless steel fixing clips
- Supplied with neutral white [4000K]
- CRI: Ra>80

Note: This luminaire is not suitable for all chemical environments, please contact us for advice if this luminaire may be exposed to, oil, grease, solvents, acids, alkaline or any similar chemicals.

















## **Technical Data**

General		
Luminaire Wattage (W)	63	Rated In
Weight (kg)	2 97	Power Fa
Operating Temperature (ta °C)		Input Vol
		Inrush Cu
Light Output Lumens (Im)	8800	Conducto
Efficacy (Im/W)	140	i erminar
LED		
CCT (K)	4000	
CRI	80	
Macadam Elipses	3	
Driver		
Driver Current (mA)	1400mA	
Forward Voltage (V)	24-42	
Emergency		
Emergency Lumen Operating	160	
Emergency Wattage (W)	1	

Electrical		
Rated Input Current (A)	0.28	
Power Factor (pf)	0.98	
Input Voltage Range (VAC)	198-264	
Inrush Current Peak (A)	33.1	
Conductor Size (mm)	2.5	
Terminal Type	4 nole niano key	



# xcite LED Lighting

# **Data Sheet**



### Order Code: XCNC16HENWM3

63W - 1800mm Non Corrosive Polycarbonate Luminaire - IP65 - 3hrs Maintained Emergency - 4000K

### **Dimensions**

A (mm)	1830
B (mm)	100
C (mm)	101

### Line Drawing





