# xcite LED Lighting

## **Data Sheet**



### Order Code: XCNC16NWHFS

38W - 1800mm Non Corrosive Polycarbonate Luminaire - IP65 - Microwave Sensor - 4000K

#### **Features**

- · Ideal for replacement of linear fluorescent fixtures
- · Available in 3 lengths
- Microwave movement sensor available
- Up to 118 lumens per watt efficacy

## Construction

- Grey polycarbonate body
- Supplied with opal diffuser
- Integral emergency option available
- Stainless steel fixing clips
- CRI: Ra>80
- Supplied with neutral white [4000K]

Note: This luminaire is not suitable for all chemical environments, please contact us for advice if this luminaire may be exposed to, oil, grease, solvents, acids, alkaline or any similar chemicals.















## **Technical Data**

	Electrica	I
38	Rated Input Current (A)	0.17
3.07	Power Factor (pf)	0.97
-20 to 25	Input Voltage Range (VAC)	198-264
	Inrush Current Peak (A)	20.2
4600	Conductor Size (mm)	2.5
118	Terminal Type	3 pole piano key
4000		
80		
3		
950mA		
24-42		
	3.07 -20 to 25  4600 118  4000 80 3	38 Rated Input Current (A)  3.07 Power Factor (pf)  -20 to 25 Input Voltage Range (VAC)  Inrush Current Peak (A)  Conductor Size (mm)  118  Terminal Type  4000  80  3

# xcite LED Lighting

## **Data Sheet**



## Order Code: XCNC16NWHFS

38W - 1800mm Non Corrosive Polycarbonate Luminaire - IP65 - Microwave Sensor - 4000K

### **Dimensions**

A (mm)	1830
B (mm)	100
C (mm)	101

## Line Drawing





