xcite LED Lighting

Data Sheet



Order Code: XCNC16NWHFSM3

38W - 1800mm Non Corrosive Polycarbonate Luminaire - IP65 - Microwave Sensor - 3hrs Maintained Emergency - 4000K



- · Available in 3 lengths
- Microwave movement sensor available
- Up to 118 lumens per watt efficacy

Construction

- Grey polycarbonate body
- Supplied with opal diffuser
- Integral emergency option available
- Stainless steel fixing clips
- CRI: Ra>80
- Supplied with neutral white [4000K]

Note: This luminaire is not suitable for all chemical environments, please contact us for advice if this luminaire may be exposed to, oil, grease, solvents, acids, alkaline or any similar chemicals.





















Technical Data

General		
Luminaire Wattage (W)	38	Rat
Weight (kg)	3.07	Pov
Operating Temperature (ta °C)	5 to 25	Inp
Light Output		Inru Cor
Lumens (lm)	4600	
Efficacy (lm/W)	118	Ter
LED		
CCT (K)	4000	
CRI	80	
Macadam Elipses	3	
Driver		
Driver Current (mA)	950mA	
Forward Voltage (V)	24-42	
Emergency		
Emergency Lumen Operating	160	
Emergency Wattage (W)	1	

Electrical		
Rated Input Current (A)	0.17	
Power Factor (pf)	0.97	
Input Voltage Range (VAC)	198-264	
Inrush Current Peak (A)	20.2	
Conductor Size (mm)	2.5	
Terminal Type	4 pole piano key	



xcite LED Lighting

Data Sheet



Order Code: XCNC16NWHFSM3

38W - 1800mm Non Corrosive Polycarbonate Luminaire - IP65 - Microwave Sensor - 3hrs Maintained Emergency - 4000K

Dimensions

A (mm)	1830
B (mm)	100
C (mm)	101

Line Drawing





