xcite LED Lighting

Data Sheet



0.17 0.97 198-264 20.2 2.5

4 pole piano key

Order Code: XCNC16NWM3

38W -1800mm Non Corrosive Polycarbonate Luminaire - IP65 - 3hrs Maintained Emergency - 4000K

Features

- · Ideal for replacement of linear fluorescent fixtures
- · Available in 3 lengths
- Microwave movement sensor available
- Up to 118 lumens per watt efficacy

Construction

- Grey polycarbonate body
- Supplied with opal diffuser
- Integral emergency option available
- Stainless steel fixing clips
- CRI: Ra>80
- Supplied with neutral white [4000K]

Note: This luminaire is not suitable for all chemical environments, please contact us for advice if this luminaire may be exposed to, oil, grease, solvents, acids, alkaline or any similar chemicals.

















Technical Data

	Electrical
38	Rated Input Current (A)
2.07	Power Factor (pf)
	Input Voltage Range (VAC)
	Inrush Current Peak (A)
4600	Conductor Size (mm)
118	Terminal Type
4000	
80	
3	
950mA	
24-42	
160	
1	
	2.97 5 to 25 4600 118 4000 80 3 950mA 24-42

xcite LED Lighting

Data Sheet



Order Code: XCNC16NWM3

38W -1800mm Non Corrosive Polycarbonate Luminaire - IP65 - 3hrs Maintained Emergency - 4000K

Dimensions

A (mm)	1830
B (mm)	100
C (mm)	101

Line Drawing





