

**Order Code: XCNC24NW**

42W - 1200mm Twin Body Non Corrosive Polycarbonate Luminaire - IP65 - 4000K



**Features**

- Ideal for replacement of linear fluorescent fixtures
- Available in 3 lengths
- Microwave movement sensor available
- Up to 121 lumens per watt efficacy

**Construction**

- Grey polycarbonate body
- Supplied with opal diffuser
- Integral emergency option available
- Stainless steel fixing clips
- Supplied with neutral white [4000K]
- CRI: Ra>80



Note: This luminaire is not suitable for all chemical environments, please contact us for advice if this luminaire may be exposed to, oil, grease, solvents, acids, alkaline or any similar chemicals.

**Technical Data**

General		Electrical	
Luminaire Wattage (W)	42	Rated Input Current (A)	0.19
Weight (kg)	2.59	Power Factor (pf)	0.97
Operating Temperature (ta °C)	-20 to 25	Input Voltage Range (VAC)	198-264
Light Output		Inrush Current Peak (A)	20.02
		Lumens (lm)	5100
		Conductor Size (mm)	2.5
Efficacy (lm/W)	121	Terminal Type	3 pole piano key
<b>LED</b>			
CCT (K)	4000		
CRI	80		
Macadam Ellipses	3		
<b>Driver</b>			
Driver Current (mA)	1000mA		
Forward Voltage (V)	24-40		

**Order Code: XCNC24NW**

42W - 1200mm Twin Body Non Corrosive Polycarbonate Luminaire - IP65 - 4000K

Dimensions

A (mm)	1260
B (mm)	154
C (mm)	95

Line Drawing

