

## Order Code: XCNC24NWHFSM3

42W - 1200mm Twin Body Non Corrosive Polycarbonate Luminaire - IP65 - Microwave Sensor - 3hrs Maintained Emergency - 4000K



## Features

- Ideal for replacement of linear fluorescent fixtures
- Available in 3 lengths
- Microwave movement sensor available
- Up to 121 lumens per watt efficacy

## Construction

- Grey polycarbonate body
- Supplied with opal diffuser
- Integral emergency option available
- Stainless steel fixing clips
- CRI: Ra>80
- Supplied with neutral white [4000K]

Note: This luminaire is not suitable for all chemical environments, please contact us for advice if this luminaire may be exposed to, oil, grease, solvents, acids, alkaline or any similar chemicals.

## Technical Data

## General

Luminaire Wattage (W)	42
Weight (kg)	2.69
Operating Temperature (ta °C)	5 to 25

## Light Output

Lumens (lm)	5100
Efficacy (lm/W)	121

## LED

CCT (K)	4000
CRI	80
Macadam Ellipses	3

## Driver

Driver Current (mA)	1000mA
Forward Voltage (V)	24-40

## Emergency

Emergency Lumen Operating	160
Emergency Wattage (W)	1

## Electrical

Rated Input Current (A)	0.19
Power Factor (pf)	0.97
Input Voltage Range (VAC)	198-264
Inrush Current Peak (A)	20.02
Conductor Size (mm)	2.5
Terminal Type	4 pole piano key

**Order Code: XCNC24NWHFSM3**

42W - 1200mm Twin Body Non Corrosive Polycarbonate Luminaire - IP65 - Microwave Sensor - 3hrs Maintained Emergency - 4000K

**Dimensions**

A (mm)	1260
B (mm)	154
C (mm)	95

**Line Drawing**