xcite LED Lighting


Data Sheet



Order Code: XCNC24NWHFSM3

42W - 1200mm Twin Body Non Corrosive Polycarbonate Luminaire - IP65 - Microwave Sensor - 3hrs Maintained Emergency -4000K





- Microwave movement sensor available
- Up to 121 lumens per watt efficacy

Construction

Features

- Grey polycarbonate body
- Supplied with opal diffuser
- Integral emergency option available
- Stainless steel fixing clips
- CRI: Ra>80
- Supplied with neutral white [4000K]

















Note: This luminaire is not suitable for all chemical environments, please contact us for advice if this luminaire may be exposed to, oil, grease, solvents, acids, alkaline or any similar chemicals.

Technical Data

General			Ele
Luminaire Wattage (W)	42	Rated Input Current (A)	
Weight (kg)	2 69	Power Factor (pf)	
Operating Temperature (ta °C)		Input Voltage Range (VAC)	
		Inrush Current Peak (A)	
Light Output Lumens (Im)	5100	Conductor Size (mm)	
Efficacy (Im/W)	121	Terminal Type	
LED			
CCT (K)	4000		
CRI	80		
Macadam Elipses	3		
Driver			
Driver Current (mA)	1000mA		
Forward Voltage (V)	24-40		
Emergency			
Emergency Lumen Operating	160		
Emergency Wattage (W)	1		

Electrical		
Rated Input Current (A)	0.19	
Power Factor (pf)	0.97	
Input Voltage Range (VAC)	198-264	
Inrush Current Peak (A)	20.02	
Conductor Size (mm)	2.5	
Terminal Type	4 pole piano key	

xcite LED Lighting

Data Sheet



Order Code: XCNC24NWHFSM3

42W - 1200mm Twin Body Non Corrosive Polycarbonate Luminaire - IP65 - Microwave Sensor - 3hrs Maintained Emergency - 4000K

Dimensions

A (mm)	1260
B (mm)	154
C (mm)	95

Line Drawing

