# xcite LED Lighting

### **Data Sheet**



0.19 0.97 198-264 20.02 2.5

4 pole piano key

### Order Code: XCNC24NWM3

42W - 1200mm Twin Body Non Corrosive Polycarbonate Luminaire - IP65 - 3hrs Maintained Emergency - 4000K

- · Ideal for replacement of linear fluorescent fixtures
- · Available in 3 lengths
- Microwave movement sensor available
- Up to 121 lumens per watt efficacy

#### Construction

- Grey polycarbonate body
- Supplied with opal diffuser
- Integral emergency option available
- Stainless steel fixing clips
- CRI: Ra>80
- Supplied with neutral white [4000K]

Note: This luminaire is not suitable for all chemical environments, please contact us for advice if this luminaire may be exposed to, oil, grease, solvents, acids, alkaline or any similar chemicals.

















### **Technical Data**

Tooliinoar Data			yai Bata
	General		Electrical
Luminaire Wattage (W)		42	Rated Input Current (A)
Weight (kg)		2.59	Power Factor (pf)
Operating Temperature (ta °C)		5 to 25	Input Voltage Range (VAC)
Lumens (Im)	Light Output		Inrush Current Peak (A)
		5100	Conductor Size (mm)
Efficacy (lm/W)		121	Terminal Type
	LED		
CCT (K)		4000	
CRI		80	
Macadam Elipses		3	
	Driver		
Driver Current (mA)		1000mA	
Forward Voltage (V)		24-40	
	Emergency		
Emergency Lumen Opera	ting	160	
Emergency Wattage (W)		1	

# xcite LED Lighting

## **Data Sheet**



### Order Code: XCNC24NWM3

42W - 1200mm Twin Body Non Corrosive Polycarbonate Luminaire - IP65 - 3hrs Maintained Emergency - 4000K

### **Dimensions**

A (mm)	1260
B (mm)	154
C (mm)	95

### Line Drawing





