xcite LED Lighting

Data Sheet



0.27 0.98 198-264 33.1 2.5

4 pole piano key

Order Code: XCNC25NWM3

65W - 1500mm Twin Body Non Corrosive Polycarbonate Luminaire - IP65 - 3hrs Maintained Emergency - 4000K

- · Ideal for replacement of linear fluorescent fixtures
- · Available in 3 lengths
- Microwave movement sensor available
- Up to 123 lumens per watt efficacy

Construction

- Grey polycarbonate body
- Supplied with opal diffuser
- Integral emergency option available
- Stainless steel fixing clips
- CRI: Ra>80
- Supplied with neutral white [4000K]

Note: This luminaire is not suitable for all chemical environments, please contact us for advice if this luminaire may be exposed to, oil, grease, solvents, acids, alkaline or any similar chemicals.

















Technical Data

Technical Data		
General		Electrical
Luminaire Wattage (W)	65	Rated Input Current (A)
Weight (kg)	3.31	Power Factor (pf)
Operating Temperature (ta °C)	5 to 25	Input Voltage Range (VAC)
Light Output		Inrush Current Peak (A)
Light Output Lumens (Im)	8000	Conductor Size (mm)
Efficacy (lm/W)	123	Terminal Type
Lineacy (III/VV)	125	
LED		
CCT (K)	4000	
CRI	80	
Macadam Elipses	3	
Driver		
Driver Current (mA)	1400mA	
Forward Voltage (V)	24-42	
Emergency		
Emergency Lumen Operating	160	
Emergency Wattage (W)	1	

xcite LED Lighting

Data Sheet



Order Code: XCNC25NWM3

65W - 1500mm Twin Body Non Corrosive Polycarbonate Luminaire - IP65 - 3hrs Maintained Emergency - 4000K

Dimensions

A (mm)	1560
B (mm)	154
C (mm)	95

Line Drawing





