

**Order Code: XCNC26NW**

77W - 1800mm Twin Body Non Corrosive Polycarbonate Luminaire - IP65 - 4000K



**Features**

- Ideal for replacement of linear fluorescent fixtures
- Available in 3 lengths
- Microwave movement sensor available
- Up to 123 lumens per watt efficacy

**Construction**

- Grey polycarbonate body
- Supplied with opal diffuser
- Integral emergency option available
- Stainless steel fixing clips
- CRI: Ra>80
- Supplied with neutral white [4000K]



Note: This luminaire is not suitable for all chemical environments, please contact us for advice if this luminaire may be exposed to, oil, grease, solvents, acids, alkaline or any similar chemicals.

**Technical Data**

General		Electrical	
Luminaire Wattage (W)	77	Rated Input Current (A)	0.34
Weight (kg)	4.28	Power Factor (pf)	0.98
Operating Temperature (ta °C)	-20 to 25	Input Voltage Range (VAC)	198-264
		Inrush Current Peak (A)	39.52
		Conductor Size (mm)	2.5
		Terminal Type	3 pole piano key
Light Output			
Lumens (lm)	9500		
Efficacy (lm/W)	123		
LED			
CCT (K)	4000		
CRI	80		
Macadam Ellipses	3		
Driver			
Driver Current (mA)	1400mA		
Forward Voltage (V)	36-52		

**Order Code: XCNC26NW**

77W - 1800mm Twin Body Non Corrosive Polycarbonate Luminaire - IP65 - 4000K

Dimensions

A (mm)	1830
B (mm)	158
C (mm)	102

Line Drawing

