

Order Code: XCNC2X1M3MS
600mm - CCT [3000K/4000K/6000K] + Wattage Selectable - Emergency - Microwave sensor



Features

- Suitable for a range of commercial and industrial applications
• Available in 4 lengths [2ft, 4ft, 5ft, and 6ft]
• CCT [3000K/4000K/6000K] adjustable via 3-way selector switch
• Wattage [11 to 18] adjustable via 2-way dip switch
• Position adjustable mounting clips
• Stainless steel retainer clips for diffuser with anti-tamper screw

Construction

- Grey polycarbonate body
• Weatherproof IP65 construction
• Modular emergency and sensor pack for quick and easy conversion

Installation Notes

Conduit and BESA fixing points for end or rear cable entry
Loop in/out push-fit terminal block for quick installation



Technical Data

General

Table with 2 columns: General, Luminaire Wattage (W), Weight (kg), Operating Temperature (ta °C)

Light Output

Table with 2 columns: Light Output, Lumens (lm), Efficacy (lm/W)

LED

Table with 2 columns: LED, CRI, Macadam Elipses

Driver

Table with 2 columns: Driver, Driver Current (mA), Forward Voltage (V)

Emergency

Table with 2 columns: Emergency, Emergency Lumen Operating, Emergency Wattage (W)

Electrical

Table with 2 columns: Electrical, Rated Input Current (A), Power Factor (pf), Input Voltage Range (VAC), Inrush Current Peak (A), Conductor Size (mm), Terminal Type

**Order Code:** XCNC2X1M3MS  
600mm - CCT [3000K/4000K/6000K] + Wattage Selectable - Emergency - Microwave sensor

Dimensions

A (mm)	675
B (mm)	80
C (mm)	95
Fix	400

Line Drawing

